



W20-1
48" x 48"



W20-4
48" x 48"



W20-7a(1)
48" x 48"



NOTE: ACCESS POINTS WITHIN LANE CLOSURE SHALL BE CONTROLLED BY FLAGGER(S)

REFER TO TCP 100.01 FOR SIGN SPACING, TAPER LENGTHS AND BUFFER ZONE LENGTHS



DY CL



B A



W20-1
48" x 48"



W20-7a(1)
48" x 48"



DY CL

BUFFER

WORK AREA


BUFFER

A B



W20-7a(1)
48" x 48"

W20-4
48" x 48"



W20-1
48" x 48"

DIRECTION OF TRAFFIC



SIGN



WORK SITE



FLAGGER



TRAFFIC DRUMS OR CONES

S¹=30 FT.

S²=10 FT.

REVISION BY	DATE	APPROVED

DATE	07-01-04	TRAFFIC OPERATIONS SECTION MONTGOMERY COUNTY, MARYLAND
DES. BY	MCDPWT	
DRAWN BY	TCLE	FLAGGING CONTROL AT 3 - LEG INTERSECTION (1)
SCALE	NTS	APPROVED
		CHIEF, TRAFFIC OPERATIONS SECTION
		STANDARD TCP-105.03 OF SHEETS